

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number  
**WO 2005/018835 A1**

(51) International Patent Classification<sup>7</sup>: **B07C 5/36, 5/10**

[AU/AU]; 182 St. Vincents Road, Banyo, Queensland 4014 (AU).

(21) International Application Number:

PCT/AU2004/001135

(74) Agent: **PIZZEYS PATENT AND TRADE MARK ATTORNEYS**; Level 14, ANZ Centre, 324 Queen Street, Brisbane, QLD 4000 (AU).

(22) International Filing Date: 25 August 2004 (25.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003904534 25 August 2003 (25.08.2003) AU

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US):  
**AUSTRALIAN INSPECTION TECHNOLOGIES**  
[AU/AU]; 182 St. Vincents Road, Banyo, Queensland 4014 (AU).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BLAGDEN, Troy**

[Continued on next page]

(54) Title: **SORTING APPARATUS AND METHODS**



(57) Abstract: There is provided sorting apparatus wherein a particulate product stream (25) passes a concentrator (26) to feed product onto a conical dispersion plate (27) which delivers the product evenly in an annular mono-layer to a collimator comprising inner (30) and outer (31) product guides to produce, an annular, vertically directed product flow (32). Located within the annulus of the product flow (32) is a detector assembly comprising an upper detector and optics box (33) beneath which is mounted for rotation a beam splitting mirror (34) driven by a motor (35) and scanning product in the annular detection area (36). The product passing through the detection area (36) is bombarded with a source and the reflected or transmitted intensity signal (37) is then measured by a detector in the detector and optics box (33). The classified product is removed from the product stream via a rejector (40) operable in response to control means directed by the detector in the detector and optics box (33). The classified product (41) passes into a chute (42) to one side of a separation plate (43). The remaining product continues unhindered into the chute (44).



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

— *with amended claims*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*